



THE PICOTE MINI MILLER

Easy to Move, Hard to Beat



The Mini Miller is a high speed, high torque unit designed for cleaning, descaling, and removing roots in pipes between DN50-100 (2-4") pipes and for cutting/reinstatements in DN50-75 (2-3") pipe. When paired with the Picote Mini Coating Pump it is capable of brush coating in DN50-150 (2-6") pipes as well.

Weighing only 27kg (60lbs), it's 8mm (1/3") shaft has a reach of 16m (50'), which can be extended 10m (33') by adding a shaft extension.

It is fed by a standard 3 prong wall outlet making it a very easy to use on almost any jobsite.

USES AND BENEFITS

- Designed to take up as little space as possible while covering a large range of applications.
- Time is money and the lightweight Mini Miller takes less time to transport and maneuver into position on jobsites.
- High Speed/High Torque: 500-2900 rpm.
- Lightweight: 27kg (60lbs)
- The standard safety features include a safety clutch, internal GFI, protective outer shaft casing, and an E-stop help to keep you and your equipment investment protected.
- Mini Cleaner +C camera upgrade available.

Mini Miller Technical Specifications	
Pipe Size Ranges	
Cleaning / Descaling	DN50-100 (2-4")
Cutting / Reinstatement	DN50-75 (2-3")
Picote Brush Coating™	DN50-150 (2-6")
Usable Shaft Length	16m (50')
Cable Extensions	10m (32.8 ft)
Shaft Size	8mm (1/3")
Casing Type	Thick
Output Power (Watts)	1100W
Speed (RPM)	500-2900
Power	UK/US: 110/125V, 15 Amp EU: 220/230V, 16 Amp
Weight	27kg (60 lbs)
Size	740 x 519 x 404mm 29 x 20 x 16"
Safety Features	Protective shaft casing, operator presence foot control, internal GFI, manual safety clutch, & emergency stop



More Info/Guides/Technical Support:

- Visit picoteinstitute.com for e-learning courses, educational videos, quick guides, & manuals.
- For more information on products, spare parts, assembly and operation, consult the Mini Miller Manual or contact Picote Technical Support.
- For hands-on product training, Picote operates training centers in USA, UK, and Finland.

PRODUCTS AND SPARE PARTS

Picote Mini Miller Products and Parts	
PN	Description
3540000817	Mini Miller
3540000817US	Mini Miller 110v (US)
1312030085017	Mini Miller - 8mm (1/3") Shaft with Thick Casing 17.4m (57.4')
9331008000	Thick outer casing for 8mm (1/3") shaft
900000856	Micro/Mini Miller Safety Clutch
900000920	Silicone Spring for Micro/Mini Miller (5 pcs)
9530000041	Safety Clutch Upgrade Kit for Micro/Mini Miller
9530000134	Strain Relief Micro/Mini Miller 9/13mm casing
9530000134-1	Strain Relief Spring Micro/Mini Miller for Safety Clutch
9530000045	Micro/Mini Miller Handle Upgrade Kit