

## PICOTE TWISTER FAMILY



### Twister Mini Flexi

Extremely agile Twister that makes difficult reinstatements through p-traps accessible.

Sizes: DN50 & 70/75 (2 & 3")  
Shaft Size: 8mm (1/3")  
Use with Mini Cleaner



### Twister Mini Express

Compact version of the Twister Express for reinstatements in small diameter pipes.

Sizes: DN50 & 70/75 (2 & 3")  
Shaft Size: 8mm (1/3")  
Use with Mini Miller



### Twister Express

Our most efficient reinstatement Twister. Great for multiple reinstatements per day.

Sizes: DN100 (4")  
Versions: lined & unlined  
Shaft Size: 12mm (1/2")



### Twister Standard

Designed for connection reinstatements and is highly versatile and consistent.

Sizes: DN100, 150, & 200 (4, 6, & 8")  
Versions: lined & unlined  
Shaft Size: 12mm (1/2")



### Twister Liner Remover

Designed to remove failed linings. 3mm thick front metal panel, dual front brushes, and aggressive carbide help make short work of lining removal.

Sizes: DN100 & 150 (4 & 6")  
Shaft Size: 12mm (1/2")



### Twister Metal Grinder

Quickly and efficiently grinds away most metal including rebar, steel rods, nails, screws, and lead joints without damaging the host pipe.

Sizes: DN100 (4")  
Shaft Size: 12mm (1/2")



### Twister Cleaner

Designed for light cleaning and working in plastic & fragile pitch fiber & Orangeburg pipe.

Sizes: DN100 (4")  
Shaft Size: 12mm (1/2")



### Twister Concrete Remover

Dual front brushes provide stability, heavy duty front panel with large carbides and specialized front drill head combine for efficient concrete, grout, slurry, & rock removal.

Sizes: DN100 & 150 (4 & 6")  
Shaft Size: 12mm (1/2")  
Sizes: DN150, 200, 225 (6, 8 & 9")  
Shaft Size: 18mm (3/4")



### Twister Power+

Designed for the Maxi Power+ and working in larger pipes for reinstatements and cleaning.

Sizes: DN150, 200, 225, 250, & 300 (6, 8, 9, 10, & 12")  
Shaft Size: 18mm (3/4")  
Use with Maxi Power+