

SeeSnake® Wi-Fi Enabled Monitors and Recorders



RIDGID® SEESNAKE CS12X DIGITAL RECORDING MONITOR

The RIDGID SeeSnake CS12x Monitor is an all-in-one inspection reporting solution and features the largest screen of the CSx series monitors. Allow customers to see the inspection in real-time by connecting the CS12x to a mobile device using the free HQx® Live app. The dual battery option gives you long-lasting power in the field to get the job done.

FEATURES

- Runs from one or two batteries to deliver maximum run time at the job site (not swappable during use).
- At 12.1" and with a resolution of 1024 × 768 pixels, the high-contrast display is crisp, clear and daylight readable.
- TiltSense™ displays the camera's degree of tilt from horizontal when connected to a SeeSnake camera reel with TruSense™.
- Cradle and grip surface designed to hold a tablet when using the free HQx Live mobile app.
- Deep recessed pocket for storing a user-supplied external storage device.
- Docks to the SeeSnake MAX™ rM200 reel for easy transport.

SPECIFICATIONS

- Length – 19.9" (506 mm)
- Width – 15.5" (394 mm)
- Height – 11.9" (302 mm)
- Display – 12.1" (307 mm) Color LCD
- Display Resolution – 1024 × 768 (VGA)
- Power Source – 18 V Advanced Lithium Battery or AC Adapter
- Operating Temperature – 14°F to 122°F (-10°C to 50°C)
- Storage Temperature – -4°F to 140°F (-20°C to 60°C)
- Media Transfer – USB Drive or Wi-Fi via HQx Live
- Audio – Integrated Microphone and Speaker
- Autolog Format – MPEG4 (H.264)
- Photo Format – JPEG
- Video Format – MPEG4 (H.264)

Catalog No.	Description	Weight	
		lb	kg
57278	CS12x Digital Recording Monitor	13.9	6.3
57288	CS12x Monitor w/2 Batteries and 1 Charger	17.7	8
45363	AC Battery Adapter	1	0.5
44693	18 V Advanced Lithium 2.0 Ah Battery	1	0.5
44698	18 V Advanced Lithium 4.0 Ah Battery	1.5	0.7
43458	18 V Advanced Lithium Battery Charger	1.8	0.8

