

## SeeSnake® Reels and Cameras

**NEW**  
COMING IN 2019



SeeSnake Mini Reel



### RIDGID® SEESNAKE MINI WITH TRUSENSE™

The SeeSnake Mini camera reel is the smaller version of the SeeSnake Standard system, now available with TruSense technology.



**Best Use:** The Mini's moderately stiff push cable strikes a good balance between stiffness and the ability to navigate turns. This system is a workhorse, and is available with 200' (61 m) of cable.

#### FEATURES

- Rugged, high-intensity LEDs for exceptional viewing and long life.
- Self-leveling camera head option to keep the image upright.
- Powerful FleXmitter® sonde has longer range and preserves the camera's ability to make turns.
- High dynamic range (HDR) image sensor offers bright, clear in-pipe imaging in difficult lighting conditions.
- TiltSense Sensor displays the camera's pitch in a pipe on a connected SeeSnake CSx series monitor.
- Included pipe guides center the camera for better in-pipe imaging.

#### SPECIFICATIONS

SPECIFICATIONS	SeeSnake Mini	
	Rated Pipe Capacity	1.5" to 8" (38 mm to 203 mm)
<b>CABLE</b>		
Max Cable Length	200' (61 m)	200' (61 m)
Minimum Bend Radius	3" (76 mm)	3" (76 mm)
<b>CAMERA</b>		
Style	Fixed TruSense	Self-Leveling TruSense
Diameter	1.2" (30 mm)	1.2" (30 mm)
Length	1.3" (32 mm)	1" (25 mm)
<b>SONDE</b>		
Frequency	512 Hz	512 Hz
Type	FleXmitter	FleXmitter
<b>DISTANCE MEASUREMENT</b>		
Type	TruSense Counter	TruSense Counter
Data-Enabled	Two-Way	Two-Way

Catalog No.	Description	Weight	
		lb	kg
63628	200' Mini 30 mm SL TruSense	26	11.8
63633	200' Mini 30 mm TruSense	26	11.8

#### Accessories

Catalog No.	Description
67312	101 mm Star Guide, 30mm Camera, Pkg of 20
95507	75 mm Star Guide, 30 mm Camera, Pkg of 6
97462	Pipe Guide, 30 mm Camera, Pkg of 6
93392	Guide Hoop, 30 mm Camera, Pkg of 4
17558	Spanner Wrench, 30 mm



Included Star Guides help center the camera in the pipe

#### Replacement Parts

Catalog No.	Description
63843	30 mm Self-Leveling Camera Head - TruSense
63848	30 mm Fixed Camera Head - TruSense
48533	30 mm Self-Leveling Camera Head - NTSC
14083	30 mm Fixed Camera Head - NTSC
67327	200' SeeSnake Mini Push Cable Assembly
67307	Interconnect Cable, 10' Mini SeeSnake